RFeye®

SiLVUS TECHNOLOGIES
a Motorola Solutions Company

DATA SHEET

RFEYE NODE 100-18

INTELLIGENT WIDEBAND RECEIVER

The RFeye Node 100-18 offers class-leading RF performance for advanced capability, real-time spectrum operations or deployment on any spectrum critical site.

The RFeye Node 100-18 offers the capabilities of the Node 100-8 but with extended frequency range up to 18 GHz. Like the other RFeye Nodes in the family, it is a complete spectrum monitoring and geolocation system designed for remote deployment in distributed networks both indoors and outdoors, including in hostile environments. Packaged in a compact, rugged and weatherproof housing, it has been optimized for size, weight and power (SWaP) and is simple to connect to power and network.

The Node 100-18 is characterized by outstanding phase noise, noise figure, channel re-tune time and spurious free dynamic range parameters, well above any other product in its class. Its multi-mission capability allows multiple concurrent measurements and geolocations to be performed and multiple users to connect simultaneously from remote locations.

SPECIFICATIONS

Single channel receiver	
Switchable RF inputs	3 x SMA connectors
Frequency	
Range	9 kHz to 18 GHz
Noise figures at maximum sensitivity (typical)	
9 kHz to 85 MHz	8 dB
85 MHz to 1GHz	5.5 dB
1 GHz to 2.9 GHz	5 dB
2.9 GHz to 5.9 GHz	6 dB
5.9 GHz to 10 GHz	7.5 dB
10 GHz to 15 GHz	11 dB
15 GHz to 16 GHz	12 dB
16 GHz to 17 GHz	14 dB
17 GHz to 18 GHz	17 dB
Phase noise at 20kHz offset (typical)	
Receiver input at 1 GHz	-126 dBc/Hz.
Receiver input at 5 GHz	-121 dBc/Hz.
Receiver input at 18 GHz	-110 dBc/Hz.
Signal analysis	
Instantaneous bandwidth	100 MHz
Tuning resolution	1 Hz
Internal frequency reference	
Initial accuracy @20°C	±0.1 ppm typ.
Stability over temperature	±0.3 ppm
Ageing over 1 day	±0.04 ppm
Programmable sweep modes	
Sweep speed at 2 MHz RBW	390 GHz/s typ.
Sweep speed at 61 kHz RBW	320 GHz/s typ.
User programmable modes	free run continuous, single timed, user trigger, adaptive
Trigger-on-event modes	user defined masks, actions alarms
Sampling	
Resolution	16 bits per channel (I&Q)
Rate	125 MS/s I&Q
Third order intercept points with AGC	
≤ 1 GHz	+20 dBm typical
> 1 GHz to ≤ 6 GHz	+15 dBm typical
> 6 GHz to ≤ 18 GHz	+20 dBm typical

Local oscillator	
Re-radiation	≤ -90 dBm typical
Frequency references	
Selectable	Internal, GPS or external
External input	10 MHz ±10 ppm
GPS holdover *(option)*	Sync Backup Module ± 1.5µs / 24 hours
Processor sub-system	
CPU	Intel E3845 quad core
I/O	
Network	1 x 1 GigE, with POnE
Universal Serial Bus	1 x USB3.0, 1 x USB2.0
2 x expansion ports configurable as:	2 x SyncLinc with < 10 ns RMS accuracy typical, trigger input, external peripheral control
GPS antenna input	1 x SMA passive or active (3.3 VDC)
Data storage	
External flash disk	via USB interfaces
System software	
Operating system	Linux
Node Apps (optional)	EMP, Detectors
Size, weight and power	
Dimensions (w, h, d) (Node only)	200 x 50 x 192 mm (7.9 x 2.0 x 7.6 inches)
Dimensions (w, h, d) (with end plates & heat sinks)	200 x 98 x 395 mm (7.9 x 3.9 x 15.6 inches)
Weight (inc heatsink)	4.2 kg (9.3 lbs)
Weight (inc noses / end plates)	6.6 kg (14.5 lbs)
DC power	12 VDC (limits 10-30V)
Power On Ethernet (POnE)	56 VDC
Power consumption	
Typical	40 W
Maximum	50 W
Environmental	
Operating temperature	-30 to +55 °C (-22 to 131 °F)
Storage temperature	-40 to +71 °C (-40 to 160°F)
Ingress protection	IP67 (with optional end plates)

SILVUS TECHNOLOGIES
a Motorola Solutions Company

Silvus Technologies UK Ltd
Unit 1, Bourn Quarter
Wellington Way
Cambridge
CB23 7FW

Silvus Technologies and RFeye are trademarks or registered trademarks of Silvus Technologies Inc. Copyright© 2026 Silvus Technologies. All rights reserved. No part of this document may be reproduced or distributed in any manner without the prior written consent of Silvus Technologies. The information and statements provided in this document are for informational purposes only and are subject to change without notice.

bsi. ISO 9001:2015 Quality Management
UK Certificate number: FS576625